

GIGASWITCH 9/20

Compact multiswitch for 20 participants for distribution of 2 orbit positions and terrestrial signals

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
blue/yellow	4019588032552	0000/3255	743 g	448 g	17,4 x 3,5 x 15 cm	26,5 x 6 x 15,5 cm

TOP FEATURES

- Gain in satellite range
- Tilt gain
- For 2 quad LNB's
- Energy saving - usable without mains adapter
- Input for terrestrial signals
- Average tap loss for sat path only 5 dB
- Terestrial: 87 ... 790 MHz (-20 dB)
- Return path: 5 ... 65 MHz (-20 dB)
- All outputs are return path compatible
- Isolation: 25 dB

AMBIENT OPERATING CONDITIONS

- Ambient temperature: -25 ... 45 °C
- Humidity: 10 ... 70 %

AMPLIFICATION

- Sat: -5 dB typical
- Terrestrial: -20 dB
- Return path: -20 dB

DECOUPLING

- Output: > 25 dB

POWER SUPPLY

- Nominal voltage: 230 V
- Frequency: 50 Hz
- Mains adapter: external 15V/1,2A

RECEPTION RANGE

- Sat: 950 ... 2.150 MHz
- Terrestrial: 5 ... 790 MHz
- Return path: 5 ... 68 MHz

TECHNICAL DATA

- Satellite inputs: 8
- Terrestrial input: 1
- Outputs: 20
- Distribution length: max. 70 m

SCOPE OF DELIVERY

GIGASWITCH 9/20, power supply (15V/1,2A), instruction manual