

DIGIPAL T2/C HD

Combo-Receiver zum Empfang von DVB-C und DVB-T2 HD

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
anthracite	4019588049383	0000/4938	790 g	240 g	18,2 x 4 x 12,6 cm	30,5 x 7,4 x 17,5 cm
silver	4019588149380	0001/4938	790 g	240 g	18,2 x 4 x 12,6 cm	30,5 x 7,4 x 17,5 cm
anthracite	4019588109384	0010/4938	790 g	240 g	18,2 x 4 x 12,6 cm	30,5 x 7,4 x 17,5 cm

TOP FEATURES

- DVB-T2 HD (H.265/HEVC), DVB-T2 (H.264) or DVB-T
- ISI mode: simplified device control
- Electronic program guide (EPG)
- Operation on 12V
- Internetradiofunktion
- Internet radio function

TECHNISAT ADDED VALUE SERVICES

- AUTOINSTALL: Yes
- ISIPRO cable: Yes

HANDLING/COMFORT

- Teletext subtitles: Yes
- Media Player: Yes
- Sleep timer: Yes
- Teletext: Yes
- Ideal for camping: Yes
- Alarm: Yes

SUPPORTED FORMATS & CODECS

- Video-Formats: MKV, MP4, MOV, MPG, MTS, TS, TS4, VOB, M2TS, AVI
- Picture-Formats: BMP, JPEG, PNG, TIFF
- Audio-Formats: AAC, MP3, M4A, MP2

DECRYPTION SYSTEM

- Irdeto: Yes

POWER CONSUMPTION

- Standby LED: < 0,3 W
- In operation: 4,7 W

CONNECTIONS

- HDMI™ (out): 1
- audio/video output analog (3.5 mm jack): Yes TechniSat specific adapter set necessary (available at 0000/3649)
- USB: 1 (USB 2.0)
- Smartcard reader: Yes
- Digital electric audio output (S/PDIF): Yes
- Ethernet 10/100 (RJ-45): Yes
- IEC-Connector: Yes

OTHER FEATURES

OSD languages: English, German, French, Greek, Italian, Lithuanian, Dutch, Polish, Portuguese, Spanish, Czech, Turkish, Hungarian, Swedish

DECODER

Video decoder: MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC, H.265/HEVC

Audio decoder: MPEG-1 & MPEG-2 Layer I, II, III

DISPLAY

Freeze frame: Yes

SD: Yes

HD: Yes

1080p: Yes

1080i: Yes

720p: Yes

576p: Yes

576i: Yes

READY FOR RECEPTION

freenetTV: Yes

TUNER

Tuner type: Single-Tuner

DVB-C Tuner: 1

Tuner DVB-T2: DVB-T2/HEVC (H.265)

DVB-T Tuner: 1

Reception on: HD-TV, SD-TV, radio

TUNER - CABLE

Reception range: 47 ... 862 MHz

Demodulation: 16 / 32 / 64 / 128 / 256 QAM

Symbol rate: 1,5 ... 7,2

FEC: Reed-Solomon (204, 188)

TUNER - TERRESTRIAL

Reception range 1: 174 ... 230 MHz

Reception range 2: 470 ... 862 MHz

Demodulation: COFDM / QPSK, 16-QAM, 64-QAM, 256-QAM

Transmission mode: 1k, 2k, 4k, 8k, 16k, 32k

Voltage supply: 5 V

Power supply: max. 0,03 A

POWER SUPPLY

Mains adapter: extern DC 12 V / 1,5 A

Nominal voltage: 230 V

Frequency: 50 Hz

SCOPE OF DELIVERY

DIGIPAL T2 HD, remote control TechniControl incl. batteries, power supply, HDMI cable, manual