

SATMAN 65 PLUS with SCR-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
yellow with Smiley	4019588888654	2565/8886	8,8 kg	5,2 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
polar white	4019588888760	2765/8886	8,8 kg	5,2 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
slate/grey	4019588888630	2365/8886	8,8 kg	5,2 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
brick/red	4019588888647	2465/8886	8,8 kg	5,2 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
beige	4019588888609	2065/8886	8,8 kg	5,2 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm

TOP FEATURES

- 65 cm Spiegel aus erstklassigem Aluminium (beidseitig pulverbeschichtet)
- Inkl. SCR-LNB
- Ausgelegt für den 6-Teilnehmer-Empfang
- 4 Teilnehmer über SCR
- 2 Teilnehmer über Legacy
- 1 Orbitposition (z. B. Astra 19,2° Ost)
- Optimal für Wand- und Dachmontage

LOCAL OSCILLATOR

- Low band: 9,75 GHz
- High band: 10,7 GHz

LNB CONTROL

- Vertical: 11,5 - 14,5 V
- Horizontal: 16 - 19 V

GENERAL CHARACTERISTICS

- Material: Aluminium
- Material strength: 1,5 mm
- Coating: Powder-coated on both sites
- Colour: beige, slate-grey, brick-red, green

INPUT FREQUENCY RANGE
Low band: 10,7 ... 11,7 GHz
High band: 11,7 ... 12,75 GHz

NOISE FACTOR
Lower frequency range: 0,6 dB max.
Upper frequency range: 0,6 dB max.

OUTPUT FREQUENCY RANGE
Low band: 950 ... 1.950 MHz
High band: 1.100 ... 2.150 MHz

PREPARED FOR
Number of orbit positions: 1
Number of clients: 6

SINGLE-CABLE OUTPUT
Output frequency: 950 ... 2.150 MHz
Number of output channels: 4
Frequency of the output channels: 1210, 1420, 1680, 2040 MHz

TECHNICAL DATA
Rated measurement: 0,65 m
F/D: 0,69
G/T: 14,5
Offset angle: 27 °
Gain: 35,7 dBi @11,3 GHz
Mast Ø: 65 mm max.
Feed reception: for UNYSAT-Universal-LNB

SCOPE OF DELIVERY
Satellite dish antenna SATMAN 65, AZ/EL bracket mount, SCR LNB, screws, installation instructions