

TECHNITENNE 60 with Twin-LNB

60 cm digital satellite antenna made of steel with twin LNB

EAN	Colour	Item no.	Weight	Device (W x H x D)	Box
4019588136823	anthracite	1360/2882	2,1 kg	56 x 65 x 50 cm	58 x 65,4 x 13,4 cm
4019588106826	light grey	1060/2882	2,1 kg	56 x 65 x 50 cm	58 x 65,4 x 13,4 cm

LOCAL OSCILLATOR
Low band: 9,75 GHz
High band: 10,6 GHz
Accuracy: ± 1 MHz
Temperature drift: ± 0,5 MHz
Phase noise: -75 @10kHz

FILTER-NAVIGATION
Features: with LNB
Number participants: 2
Diameter: 60 cm
Number satellites: 1

LNB CONTROL
Vertical: 10,5 ... 14 V
Horizontal: 16 ... 23 V
Band switch: 22 kHz

GENERAL CHARACTERISTICS
Material: steel
Material strength: 0,5 mm
Coating: painted

INPUT FREQUENCY RANGE
Low band: 10,7 ... 11,7 GHz
High band: 11,7 ... 12,75 GHz

OUTPUT FREQUENCY RANGE
Low band: 950 ... 1.950 MHz
High band: 1.100 ... 2.150 MHz

PREPARED FOR
Number of orbit positions: 1
Number of clients: 2

TECHNICAL DATA
Rated measurement: 0,56 m
F/D: 0,49
G/T: 14,5
Gain: 35,3 dBi @11.30GHz
Offset angle: 27,77 °
Mast Ø: 32 ... 50 mm
Feed reception: 40 mm
Outputs: 2
Connector type: F female
Impedance: 75 Ω
Amplification: 58 ... 64 dB (LNB)

SCOPE OF DELIVERY
TECHNITENNE 60, universal twin LNB, installation guide