

SATMAN 65 PLUS with 40 mm Quatt-Switch-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

EAN	Colour	Item no.	Device (W x H x D)	Box
4019588489059	yellow with Smiley	2565/4890	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588489004	beige	2065/4890	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588489707	polar white	2765/4890	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588489042	brick/red	2465/4890	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588489035	slate/grey	2365/4890	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm

TOP FEATURES

- 65 cm Spiegel aus erstklassigem Aluminium (beidseitig pulverbeschichtet)
- Inkl. 40 mm Quattro-Switch-LNB
- 1 bis 4 Teilnehmer
- 1 Orbitposition (z. B. Astra 19,2° Ost)
- Optimal für Wand- und Dachmontage

LOCAL OSCILLATOR

- Low band: 9,75 GHz
- High band: 10,7 GHz

LNB CONTROL

- Vertical: 11,5 - 14,5 V
- Horizontal: 16 - 19 V

GENERAL CHARACTERISTICS

- Material: Aluminium
- Material strength: 1,5 mm
- Coating: Powder-coated on both sites

INPUT FREQUENCY RANGE

- Low band: 10,7 ... 11,7 GHz
- High band: 11,7 ... 12,75 GHz

NOISE FACTOR

- Lower frequency range: 0,6 dB max.
- Upper frequency range: 0,6 dB max.

OUTPUT FREQUENCY RANGE

- Low band: 950 ... 1.950 MHz
- High band: 1.100 ... 2.150 MHz

PREPARED FOR
Number of orbit positions: 1
Number of clients: 4

TECHNICAL DATA
Rated measurement: 0,65 m
F/D: 0,69
G/T: 14,5
Offset angle: 27 °
Gain: 35,7 dBi @11,3 GHz
Mast Ø: 65 mm max.
Feed reception: for UNYSAT-Universal-LNB

SCOPE OF DELIVERY
Satellite dish antenna SATMAN 65, AZ/EL bracket mount, LNB in weather-proof housing, screws, installation instructions