


# TECHNIPRO RV 600-17E

Satellite feed-through socket for single-cable systems. Antenna socket with an isolation attenuation of 17 dB and electronic overload protection.

| EAN | Colour | Item no. | Weight (Box) | Weight | Device (W x H x D) | Box |
|---|---|---|---|---|---|---|
| 4019588031852 | silver | 0000/3185 | 102 g | 100 g | 7 x 7 x 2,5 cm | 10 x 12,5 x 1 cm |

| TRANSMISSION LOSS |
|---|
| VHF: 0,7 dB |
| UHF: 0,8 dB |
| Sat: 1,5 dB |

| FREQUENCY RANGE |
|---|
| Radio: 87,5 ... 108 MHz |
| SAT: 950 ... 2.150 MHz |
| TV: 47...68/ 118 ... 862 MHz |

| CONNECTOR TYPE |
|---|
| Radio: IEC connector (f) |
| TV: IEC connector (m) |
| SAT: F-socket |

| TAP LOSS |
|---|
| Radio: 18 dB |
| SAT: 17 dB |
| TV: 17 dB |

| SHIELDING FACTOR |
|---|
| 47 - 300 MHz: ≥ 85 dB |
| 300 - 470 MHz: ≥ 80 dB |
| 470 - 950 MHz: ≥ 75 dB |
| 950 - 2150 MHz: ≥ 55 dB |

| SCOPE OF DELIVERY |
|---|
| TechniPro RV 600-17E |