

TECHNIVISION 26 HD2

Full-HD Digital TV with eLED panel and HDTV multituner including digital DVR function via USB to record TV and radio broadcast on an external hard drive

Weight without stand	EAN	Colour	Item no.	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
6,3 kg	4019588267527	black	5026/7526	9,9 kg	6,9 kg	649 x 438 x 48 mm	64,9 x 49 x 20,5 cm	72,5 x 57,5 x 25 cm
6,3 kg	4019588267503	silver/black	5026/7506	9,9 kg	6,9 kg	649 x 438 x 48 mm	64,9 x 49 x 20,5 cm	72,5 x 57,5 x 25 cm

TOP FEATURES

- HDTV multituner
- Digital video recorder function via USB (DVRready)
- Timeshift (in conjunction with an external storage medium)
- PerfectRecording
- LED display with clock
- Common Interface Plus (CI+)

AMBIENT OPERATING CONDITIONS

- Humidity: 10 - 75 %
- Ambient temperature: 5 - 35 °C

LNB CONTROL

- Vertical: <14 V without load, > 11.5 V at 400 mA V
- Horizontal: <20 V without load, > 17.2 V at 400 mA V
- DiSEqC: DiSEqC 1.0 and 1.2 / DiSEqC 1x Sat Channel Router
- Current consumption: max (kurzschlussfest) 400 mA
- Band switch: 22 kHz

TECHNISAT ADDED VALUE SERVICES

- AUTOINSTALL: Yes

AUDIO

- Speakers: integrated broadband speaker system
- AC3 Dolby Digital bitstream out: Yes

CONNECTIONS

- HDMI™ (in): 2
- Common Interface Plus (CI+): Yes
- Digital electric audio output (S/PDIF): Yes Cinch
- Audio in/AUX in: Yes 3.5mm Klinke
- VGA: Yes
- YUV (component input): Yes Cinch
- Scart: 1 (FBAS/RGB)
- S Video: Yes
- Video IN: 1 Cinch Composite
- F socket: 1
- IEC-Connector: Yes

DECRYPTION SYSTEM

- CI+: Yes

DIMENSIONS / WEIGHT

- Weight without stand: 6,3 kg
- Set height without stand: 438 mm
- Set width without stand: 649 mm
- Set depth without stand: 48 mm

DISPLAY

- Size (cm): 66 cm
- Frequency: 50 Hz
- Format: 16:9
- Contrast ratio: 1.000:1
- Brightness: 350 cd/m²
- Response time: 8 ms
- Angle of view: 178° V / 178° H
- Freeze frame: Yes
- Resolution (vertical and horizontal): 1920 x 1080
- Type: Full-HD eLED
- Size (inches): 26
- HD: Yes
- 1080i: Yes
- 720p: Yes
- SD: Yes

HANDLING/COMFORT

- Clock: Yes
- Alarm: Yes
- Sleep timer: Yes

HOTEL MODE

- Customisable start screen: Yes
- Configurable on times: Yes
- Energy card function: Yes
- USB cloning function: Yes
- Multimedia connectors: Yes
- Menu locking: Yes
- Integrated LED clock: Yes
- Radio mode: Yes
- Mixing of channel slots: Yes
- Multicode remote control: Yes
- Fireproofed housing: Yes

MATERIALS CONTAINED

- Lead: Yes

OTHER FEATURES

- OSD languages: Polish, Spanish, French, German, Greek, Swedish, Hungarian, English, Czech, Turkish, Italian, Russian, Dutch, Portuguese
- Total programme memory: 5.000
- Regional channel selection: Yes

POWER CONSUMPTION

- Software update: 20 W
- Energy class: B
- Standby fast start: 18 W
- Standby LED: 0,6 W
- In operation: 40 W
- annual energy consumption when switched on: 58 kilowatt hour per annum
- Off status: 0 W
- Power switch: Yes
- Contains no mercury: Yes

POWER SUPPLY

- Nominal voltage: 230 V
- Mains adapter: internal
- Frequency: 50 Hz

SUPPORTED FORMATS & CODECS

- MPEG-2: Yes
- Video-Formats: TS4, TS, VOB
- JPEG: Yes
- MP3: Yes

TUNER

- Tuner type: HDTV-Multituner
- DVB-S tuner: 1
- DVB-C Tuner: 1
- DVB-T Tuner: 1
- Analogue UHF/VHF/CATV tuner: 1
- Reception on: HDTV (Mpeg-4+2) SD (MPEG-2)
- Input impedance: 75 Ω
- TECHNIROUTER ready: Yes

TUNER - ANALOGUE

- Reception range: 47 ... 862 MHz
- Video standards: B/G stereo, D/K mono, L/L'

TUNER - CABLE

- Reception range: 51 ... 858 MHz
- Demodulation: 16/32/64/128/256 QAM
- Symbol rate: 1,7 ... 7
- FEC: Reed-Solomon

TUNER - SAT

- DVB-S: 2 ... 45
- FEC: Viterbi and Reed-Solomon
- DVB-S: QPSK
- Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8
- DVB-S2: 10 ... 31
- DVB-S2: 8PSK - QPSK
- Reception range: 950 ... 2.150 MHz

TUNER - TERRESTRIAL

- Reception range 2: 470 ... 860 MHz
- Bitrate: 4 ... 32
- Power supply: 0,05 A
- Demodulation: COFDM
- Reception range 1: 174 ... 230 MHz
- Transmission mode: 2k/8k
- Voltage supply: 5 V

WALL BRACKET

- VESA wall mounting standards: VESA 100 x 100

SCOPE OF DELIVERY

TechniVision 26 HD2, Stand, 230 V mains power cable, TechniControl remote control incl. batteries, Manual